



Magna Tack

DUCT LINER SPRAY ADHESIVE & REMOVER



DATE

TECHNICAL DATA REPORT

See SDS for complete safety data

PART NO.

• MTA-1	12 oz aerosol 12/cs
• MT-LC 45LB	Large 45LB cylinder
• MTAR-SC 15LB	Small 15LB cylinder
• MR-1	1 gal 4/cs
• MR-5	5 gallons
• MR-55	55 gallons
• MB-1	1 gal 4/cs
• MB-5	5 gallons
• MB-55	55 gallons
• UMR-1	1 gal 4/cs
• UMR-5	5 gallons
• UMR-55	55 gallons
• UMB-1	1 gal 4/cs
• UMB-5	5 gallons
• UMB-55	55 gallons



DANGER

AEROSOL PRODUCTS

- Extremely flammable gas
- Contains gas under pressure; may explode if heated
- May be fatal if swallowed and enters airways
- Causes skin irritation
- Causes serious eye irritation
- Harmful if inhaled
- May cause drowsiness or dizziness
- May cause damage to organs and central nervous system through prolonged or repeated exposure

DESCRIPTION

MAGNA TACK is a high strength adhesive specially formulated to bond fiberglass insulations, urethane, rubber sheet, duct board, and bubble foil type insulation to sheet metal. It creates both permanent and temporary bonds on many surfaces. Excellent for porous or uneven surfaces as well as smooth surfaces. Waterproof, flexible, transparent, non-staining adhesive sets quickly. Effectively bonds other surfaces such as labels, cartons, floor tile, cloth, carpet, ceramic, glass, wood, Formica, leather, plastics, foam, etc. Cleans up with mineral spirits. **Aerosol (MTA-1) is LOW VOC and MIR 50 State Compliant. ALSO AVAILABLE IS A MAGNA TACK REMOVER.**

FEATURES AND BENEFITS

AEROSOL PRODUCTS

- Bonds fiberglass, urethane, rubber sheet, duct board and bubble foil to sheet metal
- Wide web spray
- Extremely Versatile
- Permanent/temp bonds
- Cleans with mineral spirits

DIRECTIONS

AEROSOL DIRECTIONS:

- Shake well before using the product.
- Remove cap.
- Point opening in the desired direction.
- Hold container 8 to 12 inches from surface to be sprayed.
- Press button to spray. For best results, apply adhesive using a side to side spraying motion.
- For temporary bonds, apply to sur-

face and allow tack to tack. Apply the material to be bonded. For permanent bonds, apply to both surfaces to be joined. Allow to tack and then press together. After use, invert can and spray until the tip is clear to prevent clogging. If adhesive accumulates around opening in spray nozzle, wipe clear while wet. If the opening becomes clogged, remove with degreasing solvent.

GALLON DIRECTIONS: Spray, brush or roll inside of sheet with light coat of adhesive. Apply a slightly thicker coat around the edges to provide enough wet strength for a good bond. You can also spray a light coat on both the insulation and the metal to use the adhesive as a contact cement.

DANGERS

Read and understand the product's label and Safety Data Sheet. Extremely Flammable Aerosol Contains gas under pressure: May explode if heated. Causes skin and eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to Nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

For Containment: Ventilate area. Contain any spills with dikes or absorbents to prevent any further migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Eliminate all sources. Ventilate area. Stop the ignition source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering.

CONTAINS

CONTENTS VARY. PLEASE REFER TO SDS FOR PRODUCT'S CONTENTS.

PRECAUTIONARY STATMENTS

AEROSOL PRODUCTS

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash hands and other exposed areas thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- In case of inadequate ventilation, wear respiratory protection.
- IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- IF ON SKIN: Wash with plenty of water.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- Call a POISON CENTER/doctor if you feel unwell.
- Get medical advice/attention if you feel unwell. Specific treatment is urgent (see First Aid on this label).
- Specific treatment (see First Aid on this label).
- Do NOT induce vomiting.
- If skin irritation occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Take off contaminated clothing and wash it before reuse.
- Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.
- Store in a well-ventilated place. Keep container tightly closed.
- Store locked up.
- Protect from sunlight. Store in a well-ventilated place.
- Dispose of contents/container to the specifications of local, regional, national, and international regulations