



May 14, 2020

## TECHNICAL DATA REPORT

See SDS for complete safety/technical data



### VAPCO PART NO.

Part Number	Size
SDS-SC	15 lb cylinder

# SPRAY DEGREASER CYLINDER

CYLINDER DEGREASER

## DESCRIPTION

**SPRAY DEGREASER CYLINDER** is a fast acting, quick drying, chlorinated hydrocarbon type solvent. Will not short motors or electrical equipment. High dielectric strength, nonexplosive, nonflammable, noncorrosive and dries clean. Pressurized can sprays solvent into hard to reach areas and instantly dissolves grease, grime, oils, waxes, gums, tars and is excellent for adhesive cleanup. Great for shops and on a job site.

## FEATURES AND BENEFITS

- Meets USDA Standards
- No Ozone Depleting Substances
- No 1,1,1 Trichloroethane
- Dissolves Grease, Grime, Oil, Waxes, Gums, Tars, Etc.

## SPECIFICATIONS

**Form:** Clear Colorless Spray | **Odor:** Chlorinated Solvent Odor | **Boiling Point:** >188°F (87°C) | **Flammability:** Not Considered a Flammable Gas by OSHA | **Vapor Pressure (mmHg):** 59 | **Vapor Density (AIR=1):** > 2 | **Evaporation Rate:** > 3 (Fast) | **Specific Gravity (H2O=1):** 1.46 | **Solids(%):** 0% | **Solubility in Water:** 0% | **Volatility Including Water (%):** 100% | **Volatile Organic Compounds (VOC):** 96% | **Decomposition Temperature:** >400°C

## LABEL INFORMATION

**SPRAY DEGREASER CYLINDER** removes grease and tough grime from any surface. Non-corrosive to metals, has low toxicity (contains no carbon tetrachloride) and is not a fire hazard. Dries fast and clean without residue. Will not short motors, generators or electrical equipment.

**DIRECTIONS:** Do not use on plastics. Harmful to some paints. Pretest in a small area. **DEGREASER AND CLEANER:** For use on refrigeration and air conditioning units and parts, engines of all types, large and small electrical motors, outboard motors, magnetos, generators, electrical equipment and contacts, kitchen exhaust fans and vents, small power and hand tools. Spray on and wipe off. **BRAKE PARTS CLEANER:** Removes fluid and grease from linings and drums. Spray brake parts liberally and wipe clean with a cloth. Follow OSHA rules fro brake parts with asbestos. DO NOT use forced air on asbestos brakes. Clean up spilled solvent immediately. **SPOT REMOVER:** Removes small grease and

oil stains from most rugs, carpets, upholstery and clothing. Spray soiled area then blot dry with an absorbent towel. It is important to pretest a small area before using a degreaser for this application.

**Dangers: Read and understand the product's label and Safety Data Sheet.** Contains gas under pressure; May explode if heated. Causes skin and eye irritation. Suspected of causing cancer. Containers of this material may be hazardous when empty. Material is heavier than air. Material may concentrate in low lying areas. This material is toxic to aquatic life

**WARNING:** This product can expose you to Tetrachloroethylene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## First Aid Measures

**Inhalation:** Move to fresh air. If not breathing administer artificial respiration, if breathing is difficult give oxygen. **Seek medical attention.**

**Skin Contact:** Take off immediately all contaminated clothing. Rinse skin with water or shower.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **Seek immediate medical attention if irritation persists.**

**Ingestion:** Rinse mouth with water. **Seek medical attention.**

## Precautions

Do NOT handle or use this product until all safety precautions have been read and understood. Keep out of the reach of children. Use only outdoors or in a well-ventilated area. Wear safety glasses and chemical resistant gloves. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Wash hands thoroughly after handling.

## Storage

**Keep out of reach of children.** Protect from sunlight. Store in a well ventilated place. Store locked up.

## In Case of Fire

Use dry chemical, foam, or Carbon Dioxide (CO2) for surrounding fire. Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

## Disposal

Dispose of in accordance with federal, state, and local regulations. Waste solvent likely considered hazardous, under RCRA, however product should be fully characterized prior to disposal. This material is toxic to aquatic life.



## CONTAINS

**SPRAY DEGREASER CYLINDER CONTAINS (CAS#) :** Tetrachloroethylene (127-18-4), Carbon Dioxide (124-38-9)

Health	2
Flammability	1
Reactivity	0
Personal	C

